

TRADE INDUST. COMPANY AB SP. Z O.O.

pl. Wolnoscy 13, Rzeszow, Poland

Telefon: +48 (575) 223 164**WhatsApp, Viber:** +48 (732) 081 224www.ticabld.comticab.mila@gmail.com

Road maintenance and construction equipment TICAB – high quality European equipment. The leading companies use the TICAB equipment in 51 countries around the world.

Universal loader TI-CAR

The **TI-CAR** loader is a universal machine. Adjustable steering wheel and comfortable seat suspension reduce the fatigue. Two pedal control system allows you to control the movement even on different areas.

TI-CAR is an effective tool for various types of work in construction, agriculture, utilities, with alternating loading into the truck, snow removal, soil removal, cargo transportation, surface leveling.

TI-CAR is multi-purpose compact machine for various applications. Almost 30 items of changing attachments make TI-CAR the most functional machine on the market

An adjustable steering wheel and a comfortable suspension seat provides a restful ride. The drive system with a foot throttle and direction pedal allows the loader to be controlled with incredible precision, even with demanding equipment and terrain. Is an effective tool where jobs vary between loading trucks, shoveling snow, and moving soil.

Technical features

Engine – Kubota, model - D1105/D905/Yanmar, model 3TNM72, (Japan), cylinders - 3,

Engine power - 19,4 kW/26 h.p,

Cylinder capacity (cm³): 1123

Cooling system - liquid;

Hydraulics - HANSA (Italy),

Battery (V-Ah): 12-60

Generator (A): 40

Maximum torque (Nm) : 72

Maximum engine speed without load - 3000 rpm;

Operating volumes

Colling system ,(l) : 5

Engine oil ,(l): 5,11

Fuel type - diesel (fuel tank - 20 l)

Hydraulic tank (l): 43

Total capacity of hydraulic system (l): 48

Running characteristics:

Travel speed - 0-13 km/h;

Frame fracture angle -56°,

Turning radius on the spot - 1.63 m.

Boom lift with flipping bucket-195-210 cm.



Capacity

Hydraulic lifting force 850 kg;
Break-out force 50 cm-800-850 kg.
Overhead load with straight frame: 850 kg
Overhead load with articulated frame: 650 kg
Overhead load, straight -950 kg.
Pulling force-950 kg.
Operating weight - 970 kg;

Wheelbase

Outer diameter of the wheels (in)-23"
Inner diameter of the disk (in)-12"
Width of the wheel (in)-8,5"

Price - 20 400 € netto

If you buy 3 or more units, you get a 5% discount!!!

COMPLETE SET:

- Cylindrical sweeping brush - **4200€;**
- Brush with waste hopper self-dumping function – **5000€**
- Transportation bucket - **590 €;**
- Jaw bucket-**610 €**
- Stacking fork - **600 €;**
- Silage fork - **1500 €.**

